

**SPÉCIFICATIONS POUDRE SÈCHE RÉGULIÈRE**

<b>VALVES</b>	<b>ALUMINIUM</b>						<b>CUIVRE. FINI CHROME</b>		
<b>Grosueur &amp; Capacité(lvs.)</b>	<b>1</b>	<b>2½</b>	<b>5</b>	<b>5½</b>	<b>10 Long</b>	<b>20</b>	<b>6</b>	<b>10 Long</b>	<b>20</b>
<b>Application</b>	<b>Buse</b>			<b>Boyau &amp; Buse</b>					
<b>Numéro de Modèle</b>	<b>A620T</b>	<b>A403T</b>	<b>A409T</b>	<b>A453</b>	<b>A457</b>	<b>A412</b>	<b>462</b>	<b>447</b>	<b>408</b>
<b>Classification ULC</b>	<b>2B :C</b>	<b>10B :C</b>	<b>10B :C</b>	<b>40B :C</b>	<b>60B :C</b>	<b>120B :C</b>	<b>40B :C</b>	<b>60B :C</b>	<b>120B :C</b>
<b>Poids au Transport (lvs.)</b>	<b>2½</b>	<b>5½</b>	<b>9¼</b>	<b>9½</b>	<b>16¾</b>	<b>38</b>	<b>13</b>	<b>18</b>	<b>39</b>
<b>Hauteur (pc.)</b>	<b>10</b>	<b>14¾</b>	<b>15¼</b>	<b>15¼</b>	<b>20</b>	<b>23¼</b>	<b>16¼</b>	<b>20½</b>	<b>24</b>
<b>Largeur (pc.)</b>	<b>3½</b>	<b>5¾</b>	<b>5½</b>	<b>7¼</b>	<b>7¾</b>	<b>10¼</b>	<b>8½</b>	<b>8¾</b>	<b>10¼</b>
<b>Diamètre (pc.)</b>	<b>2¾</b>	<b>3</b>	<b>4¼</b>	<b>4¼</b>	<b>5</b>	<b>7</b>	<b>5</b>	<b>5</b>	<b>7</b>
<b>Portée (pi.)</b>	<b>5 - 8</b>	<b>9 - 15</b>	<b>12 - 18</b>	<b>12 - 18</b>	<b>15 - 21</b>	<b>15 - 21</b>	<b>15 - 21</b>	<b>15 - 21</b>	<b>15 - 21</b>
<b>Temps d'évacuation (sec.)</b>	<b>10</b>	<b>10</b>	<b>10</b>	<b>14</b>	<b>18</b>	<b>28</b>	<b>14</b>	<b>18</b>	<b>28</b>
<b>Disponible avec Cylindre Finit Chrome</b>	<b>x</b>	<b>x</b>	<b>x</b>	<b>x</b>					
<b>Approuvé F.M.</b>		<b>x</b>	<b>x</b>		<b>x</b>	<b>x</b>	<b>x</b>	<b>x</b>	<b>x</b>
<b>Support Standard</b>	<b>Véhicule</b>	<b>Véhicule-Marine</b>		<b>Murale</b>					